



3Megapixel H.264+ Palm Size Indoor Dome Network Camera

DU-331F6-IR-LPX



- H.264+, H.264 high profile, main profile, baseline and MJPEG simultaneously
- Up to 25 / 30 fps real time at all resolution
- Fixed lens , Enhanced WDR, DIS (Digital Image Stabilization)
- Smart IR LED and ICR
- Built-in camera tampering, motion detection
- Support various protocols: RTSP, UPnP, HTTPS, Samba, SNMP, QoS
- Event trigger action: Send to NAS/Samba/FTP/Email, voice alert, notify to HTTP/TCP servers
- Power over Ethernet: IEEE 802.3af Class3

Camera

Image Device	1/2.8" 3 Mega-pixel Sony Exmor image sensor
Video Resolution	2048 x 1536 pixels
Lens	f:2.8mm
IRIS	Fixed Iris
IR LED	Yes
Angle Adjustment	Pan: -120°~120°, Tilt: 30°~90°
ICR	Yes. Auto/ Schedule/ Manual mode

Video

Video Encoder	H.264+, H.264 (base line, main-profile, and hi-profile) and MJPEG simultaneously
Video Profile	Dual stream
Frame Rate	Up to 25 / 30fps at all resolutions
Region of Interest	Multi-area ROI
Exposure Control	<ul style="list-style-type: none"> ● Auto / Auto Indoor / Manual Exposure ● BLC On/Off ● Enhanced WDR

Image Setting

- AE, AWB
- 3D / 2D Noise reduction
- Color, brightness, sharpness, contrast, Hue
- Image Mirror/Flip, 90° Rotation
- Privacy Masks
- DIS
- Pixel Count
- Anti-False Color
- Defog

On Screen Display

- Text, time and date overlay, Editable OSD
- Simultaneously multi-streaming
- Streaming over UDP, TCP, HTTP, or HTTPS
- M-JPEG streaming over HTTP (server push)
- Controllable frame rate and bandwidth
- Constant and variable bit rate
- ROI
- AOI

Streaming

Audio

Audio Encoder	RTSP: G.711 64kbps, G.726 32kbps, AAC (option, by request)
Microphone	Internal microphone
Audio Output	Line out

Network

Supported Protocols	IPv4, IPv6, TCP, UDP, HTTP, HTTPS, SMTP, FTP, NTP, DNS, DDNS, DHCP, DIPS, ARP, Bonjour, UPnP, RTSP, RTP, RTCP, IGMP, PPPoE, 3GPP, Samba, ICMP, SNMP, QoS, CoS, 802.1x, iSCSI
---------------------	--

Security

Password protection, IP address filtering, HTTPS encrypted data transmission, user access log

Users	20 simultaneous unicast users
Ethernet	10Base-T/100Base-TX auto negotiation

System Integration

Application Programming Interface	<ul style="list-style-type: none"> ● Open API for software integration ● SDK
-----------------------------------	--

Alarm Triggers

- Video motion detection
- Camera Tampering
- Audio Detection
- Digital input
- Network Disconnect

Motion Detection

10-zone video motion detection with included or excluded options

Alarm Events

- File upload via FTP or email
- File upload via Samba to NAS
- Notification via email, HTTP, and TCP
- External output activation (DO)
- Audio alert
- mSD card local storage
- Push notify to smart phone apps
- ICR On/Off

Video Buffer

Pre- and post- alarm buffering


General

Power Supply	12V DC Power over Ethernet (PoE)
PoE	IEEE 802.3af class 3
On-board Connectors	<ul style="list-style-type: none"> ● RJ-45 10Base-T/100Base(PoE) ● 12V DC terminal block ● 1 alarm input and 1 output ● External MIC in ● Audio out ● Micro SD card slot (16GB mSD card built-in) ● Reset button
Indication LED	Green and orange LEDs
Operating Temperature	-10°C to 40°C
Operating Humidity	20% ~ 80% (non-condensing)
Dimension	Height: 61mm / Diameter: 87mm
Construction	Indoor use
Viewing System	
OS	Windows® 7, 8, 10
Browser	IE 9.0 or later, Firefox or later, Safari , Google Chrome
Video Player	VLC, Quick Time, Real Player, Core Player

Software

Afidus Cloud Service™, Afidus DDNS Service™, Afidus Smart Phone Apps, Afidus NVR64™

Distributed by :



※ The product design and dimensions may change without previous notice for improvement of performance.

Dimensions

