



5 Megapixel H.264+ Smart Focus IR IP Vandal Dome

VH-532Z2 Premium



- H.264+, H.264 high profile, main profile, baseline and MJPEG simultaneously
- 5Megapixel at 25 / 30fps real time, 1080P at 50 / 60fps
- Motorized Vari-focal Lens, remote zoom and focus
- True WDR, DIS (Digital Image Stabilization)
- Built-in camera tampering, audio detection
- Support various protocols: RTSP, UPnP, HTTPS, Samba, SNMP, QoS
- Event trigger action: Send to NAS/Samba/FTP/Email, voice alert, notify to HTTP/TCP servers
- Power over Ethernet: IEEE 802.3af Class3
- IP66, IK10

Camera

Image Device	Sony Exmor™ 1/2.9" COMS Sensor
Effective Pixels	2592x1944 pixels
Lens	2.8-12 mm remote motorized zoom Lens
IRIS type	DC iris
ICR type	Mechanical
IR LED	12 pcs high light LED, Smart IR

IP Module

Video

Video Encoder	H.264+, H.264 (base line, main-profile, and hi-profile) and MJPEG simultaneously
Video Profile	3 streams simultaneously for 5M mode
Frame Rate	Up to 25 / 30fps in all resolutions for 5MP mode Up to 50/ 60fps in all resolution for 1080p mode
Exposure Control	Auto / Auto Indoor / Manual Exposure (Manual mode : 1/5~1/27,028 seconds) BLC On/Off WDR

Image Setting

- cAE, AWB
- 3D Noise reduction
- Color, brightness, sharpness, contrast, Hue
- Image Mirror/Flip, 90, rotation
- Privacy Masks
- DIS / Pixel Count
- Anti-False Color / Defog
- Overlay, Defog

Streaming

- Simultaneously multi-streaming
- Streaming over UDP, TCP, HTTP, or HTTPS
- M-JPEG streaming over HTTP (server push)
- Controllable frame rate and bandwidth
- Constant and variable bit rate
- ROI
- AOI (Higher Quality in AOI area)

Network

Supported Protocols	IPv4, IPv6, TCP, UDP, HTTP, HTTPS, SMTP, FTP, NTP, DNS, DDNS, DHCP, DIPS, ARP, Bonjour, UPnP, RTSP, RTP, RTCP, IGMP, PPPoE, 3GPP, Samba, ICMP, SNMP, QoS, CoS, 802.1x, iSCSI
Security	Password protection, IP address filtering, HTTPS encrypted data transmission, user access log
Users	20 simultaneous unicast users

Ethernet	10Base-T/100Base-TX auto negotiation
----------	--------------------------------------

System Integration

Application Programming Interface	<ul style="list-style-type: none"> ● Open API for software integration ● SDK
Alarm Triggers	<ul style="list-style-type: none"> ● Video motion detection ● Camera Tampering ● Audio Detection ● Digital input ● Network Disconnect
Motion Detection	10-zone video motion detection with included or excluded options
Alarm Events	<ul style="list-style-type: none"> ● File upload via FTP or email, SD card ● File upload via Samba to NAS ● Notification via email, HTTP, and TCP ● External output activation ● Audio alerting output ● Push notification to smart phone APP(Afidus) ● ICR On/Off

General

Power Supply	DC12V
Connectors	<ul style="list-style-type: none"> ● RJ-45 10Base-T/100Base-TX ● 12VDC (terminal block) ● 1 alarm input and 1 output (terminal block) ● Audio out (terminal block) ● External MIC input (terminal block) ● Micro SD slot ● On-Board factory default reset button/ One push focus
Indication LED	Green and orange LEDs
Operating Temperature	-10°C to 40°C
Operating Humidity	20% ~ 80% (non-condensing)


Viewing System

OS	Windows® 7, 8
Browser	IE 9.0 or later, Mozilla Firefox, Chrome, Safari
Smart phone	Android™, iPhone™
Video Player	VLC, Quick Time, Real Player, Core Player

Software

Afidus Cloud Service™, Afidus DDNS Service™, Afidus Smart Phone Apps, Afidus NVR64™

Distributed by :



※ The product design and dimensions may change without previous notice for improvement of performance.

Dimensions

